

BRITEWAY

- Compact and unobtrusive
- Long life LED technology
- Available in maintained and non maintained versions
- Axially mounted for optimum aesthetics
- Simple surface installation
- Low power consumption

Menvier Briteway is a compact low profile emergency luminaire utilising LED technology to provide an unobtrusive, low maintenance, emergency lighting solution for a wide variety of areas. Unlike traditional fluorescent emergency luminaires, Briteway is optically engineered to provide maximum performance when mounted axially, thus complementing the typical mains lighting layout. Briteway is simple to install being surface mounted and having a plug in mains connection and first fix backplate. The low energy consumption and carefully controlled light distribution of the twin, high output long life LED light sources make Menvier Briteway ideal for nightlighting or background illumination applications.



WHERE TO USE BRITEWAY

- Hospitals
- Places of entertainment
- Sheltered housing
- Student Accomodation
- Offices
- Nursing homes
- Hotels

LAMP OPTIONS

- 2 x 1W high intensity LED


MATERIALS

- Base, mounting plate and cover, fire retardant ABS, lens optical grade acrylic

INSTALLATION NOTES

- Low profile surface fixing
- First fix back plate with self locking clip on main body
- Plug in electrical connection and main body automatically locks into position when pushed into place, requires tool to remove
- Designed to provide optimum performance when mounted axially
- For 1 lux defined escape route coverage, luminaires will be mounted at typically 8m spacings.
Contact technical support for detailed spacing data.
Tel: 01302 303350

DIMENSIONS



L (mm)	W (mm)	D (mm)
198	107	36

CATALOGUE NUMBERS

System Mode	Cat. No.	Weight (kg)
Non maintained	BWN	0.6
Maintained	BWM	0.6
Intellem self check - Non maintained	BWNIS	0.6
Intellem self check - Maintained	BWMIS	0.6
Static inverter slave	BV230	0.3

Also available with Easi-Check automatic testing functionality - see page 199 for system features
Contact our customer care office for further details - 01302 303350

OPTIONS

- Maintained or Non maintained versions
- Intellem self test
- EasiCheck™

SPECIFICATION

Stand alone self contained - To specify state: Maintained / Non Maintained low profile ceiling mounted emergency luminaire, utilising dual high output white LED light sources. Optical design optimised for axial mounting. Installation via first fix back plate with plug and socket mains connector and self locking clip on body. Fully compliant with EN60598-2-22 , as Menvier Briteway range part no. _____

Self test / slave - To specify state: Low profile, ceiling mounted, Intelligent self testing / Maintained / Non Maintained / Static inverter slave luminaire with dual high output white LED light sources and optical design optimised for axial mounting. Installation via first fix back plate and fully compliant with EN60598-2-22 as Menvier Briteway range part no. _____



Simple installation via first fix back plate

EasiCheck™