

SLIMLITE

- **Shallow profile design - only 62mm deep**
- **Large format ideal for retrofit installations**
- **Optional large legend kit with 36m viewing distance**
- **Diffuser retained by screws**
- **EasiCheck™ central addressable self-test options**
- **Available in self-contained and AC/DC slave versions**

At only 62mm deep and with a softly rounded edge opal diffuser, Slimlite is an unobtrusive luminaire that is suitable for numerous interior applications. The large format design offers dual benefits. Firstly, the luminaire is ideal for use as a slim profile exit sign, using the optional legend kit. A viewing distance of up to 36m is achieved with this accessory. Additionally, decoration damage, often experienced when removing old luminaires in refurbishments, is easily covered by Slimlite. Diffusers are retained by screws ensuring that Slimlite can be confidently used in public areas, such as hotels, pubs or schools.



WHERE TO USE SLIMLITE

- Offices
- Hotels and pubs
- Restaurants
- Hospitals
- Leisure clubs
- Retail
- Universities, schools and colleges

LAMP OPTIONS

- 8W T5 fluorescent, 3500°K - G5 cap




MATERIALS

- Base - polycarbonate, white finish
- Diffuser - opal polycarbonate
- Gear cover/reflector - steel, powder coated in Permawhite finish
- Batteries (self-contained versions) - sealed nickel cadmium

INSTALLATION NOTES

- Suitable for ceiling or wall mounting
- Base fixed direct, via keyhole slots
- BESA entry on rear. Conduit entry on one side
- Gear cover/reflector retained by 2 screws
- Diffuser secured by screws
- Supplied complete with 1 x 8W lamp

DIMENSIONS



L (mm)	W (mm)	D (mm)
416	194	62

CATALOGUE NUMBERS

System Mode	Cat. No.	Weight (kg)
Non-maintained	SLO1	1.90
Maintained	SLOM	2.30
24V AC/DC Central system slave	SLO24	1.40
50V AC/DC Central system slave	SLO50	1.40
110V AC/DC Central system slave	SLO110	1.40
Description	Cat. No.	Weight (kg)
European format self-adhesive legend kit	LEXSAL	0.10

Also available with EasiCheck™ automatic testing functionality - see page 199 for system features
Contact our Technical Support and Application department for further details - 01302 303350



OPTIONS

- Maintained and non-maintained operation, 3 hour duration
- EasiCheck™ addressable testing. System detailed on page 199
- Central system slave versions

SPECIFICATION

Self contained - To specify state: BSI Kitemarked and ICEL registered, decorative 62mm deep, low profile, 3 cell self contained emergency luminaire, with opal diffuser secured by screws, as Menvier Slimlite range, part no. _____

Slave - To specify state: Central system compatible slave, decorative 62mm deep, low profile emergency luminaire, with opal diffuser secured by screws, as Menvier Slimlite range, part no. _____

PHOTOMETRIC DATA

Luminaire type	Mounting height (m)	Lux level directly under	Escape route 2m wide 1 lux min				Open (anti-panic) area 0.5 lux min			
			1	2	3	4	1	2	3	4
Self-contained										
NM	2.5	1.17	1.4	4.8	4.4	1.2	1.6	6.3	5.7	1.4
	4.0	0.46	-	-	-	-	-	-	-	-
	6.0	0.21	-	-	-	-	-	-	-	-
M	2.5	1.02	1.1	4.4	4.0	0.9	1.5	6.0	5.6	1.4
	4.0	0.40	-	-	-	-	-	-	-	-
	6.0	0.18	-	-	-	-	-	-	-	-
Slave										
AC/DC	2.5	2.24	2.3	6.6	6.2	2.2	2.3	7.9	7.2	2.1
	4.0	0.88	-	-	-	-	2.2	8.9	8.4	2.1
	6.0	0.39	-	-	-	-	-	-	-	-
AC/AC	2.5	4.10	2.3	6.4	6.2	2.2	2.2	7.3	7.1	1.6
	4.0	1.50	2.0	6.6	6.6	1.8	2.3	8.4	8.4	1.7
	6.0	0.75	-	5.4	5.2	-	1.9	9.7	9.5	1.3

See page 445 for Design Guide



Slimlite with legend