



POLITE-T HIGHWAY TUNNEL ROUTING ARMATURE

- Surface mounting, metal sheet case
- Scratch and rust resistant electrostatic powder paint
- Polycarbonate illuminated panel

POLITE-T Directional luminaire is used to mark the distance of escape doors in tunnel structures on highways with its durable structure, wall-mounted angled illuminated panels and long-life led lamps.

- IP65 protection class against dust and water.
- The mains supply voltage is standard 220 volts AC 50 Hz.
- Charging time for first use is 24 hours.
- It can withstand fluctuations up to 285 volts at mains voltage.
- It is manufactured according to TS 8710 EN60598-2-22 standard in the framework of ISO 9001-2000 quality management system.

USAGE AREAS

- Highway Tunnel

LAMP OPTIONS

- White light LED bulb, 6500 ° K

BODY STRUCTURE

- Body - Electrostatic powder black painted 1,5 mm sheet
- Label panel - 5 mm solid polycarbonate panel, latex printing on white foil
- BATTERY- Nickel-cadmium in all models

OPTIONS

- Continuous and emergency models



ISO 9001
UL-C (Certification)



2 YEAR
GUARANTEE



POLITE-T HIGHWAY TUNNEL ROUTING ARMATURE

MODEL CODE	LIGHTING STYLE	MOUNTING STYLE	LAMP	LIGHTING FACE	DURATION (minute)	DIMENSIONS (W-L-H mm)	WEIGHT	IP CLASS	ISOLATION CLASS	OPERATION TEMP	POWER CONSUMPTION	OPERATING VOLTAGE
POT-1213	Maintained	Wall Mount	2x2000lm led	Single Face	Emergency 180 m.	150x830x530mm	18,5kg	65	I	-16/+45°	35w	220-240
POT-1010	Mains Light	Wall Mount	2x2000lm led	Single Face	—	150x830x530mm	17kg	65	I	-16/+45°	30w	220-240

DIMENSIONS

