

## SFS Emergency Exit Sign Fixture



- Aluminum profile body, ABS plastic covers
- Economical exit signage
- Transparent acrylic illuminated panel

### AREAS OF USE

- Fire exit doors
- Offices
- Meeting rooms
- Reception areas
- Shopping malls
- Hotels and bars
- Restaurants
- Entertainment clubs
- Universities, dormitories, schools and colleges

### GENERAL FEATURES

- White LED bulb, 6500°K
- Housing - Aluminum profile housing, ABS plastic side covers
- Articulated mounting bracket - ABS plastic, suitable for ceiling or wall mounting
- Label panel - UV printing on transparent acrylic panel

### PRODUCT INFORMATION

- Designed for standard-compliant, economical signage applications on ceilings, walls, and above doors.
- All plastic components meet the necessary flame-retardant requirements.
- LED light sources illuminate the figure on the plexiglass through the profile.
- It is a self-contained emergency signage fixture containing its own battery and power supply.
- Manufactured in accordance with the ISO 9001-2000 quality management system and TS 8710 EN60598-2-22 standard.

STOCK	PRODUCT	WORKING METHOD	LAMP	TIME	DIMENSIONS LxWxH	weight	IP	INSULATION CLASS	WORKING temp	POWER CONS.	WORKING VOLTAGE
A20101	A201-20223E SFS EMERGENCY ESCAPE SIGN	continius on	8xF LED	180 m.	40x200x150mm	0,310kg	40	I	-16/+45°	2 w	220-240
A20102	A201-24223E SFS EMERGENCY ESCAPE SIGN	continius on	10xF LED	180 m.	40x240x170mm	0,420kg	40	I	-16/+45°	2 w	220-240
A20103	A201-24020E SFS EMERGENCY ESCAPE SIGN	energy only	10xF LED	-	40x240x170mm	0,390kg	40	I	-16/+45°	2 w	220-240
A20104	A201-30223E SFS EMERGENCY ESCAPE SIGN	continius on	10xF LED	180 m.	40x300x200mm	0,500kg	40	I	-16/+45°	2 w	220-240
A20105	A201-30020E SFS EMERGENCY ESCAPE SIGN	energy only	10xF LED	-	40x300x200mm	0,460kg	40	I	-16/+45°	2 w	220-240

